

Roof hatch RHT in special sizes, single lid

Special size: x mm

- Sizes > wider than 1200 mm are supplied with double lid (RHTD).
- Special sizes are supplied in aluminium

Product features roof hatch RHT:

- Delivered fully assembled
 - Thermal separated and insulated construction
 - Counterbalancing system for assisted opening and controlled closing
 - Wind and weather tight sealing between lid and curb
 - Lid that engages automatically in open position, with one hand release
 - Closure with Gorter hardware and stainless steel Euro cylinder lock, inside and outside operation
 - Diagonal Gorter handrail to safely enter and leave roof hatch
-
- Dimensions > 3000 mm: type RHTE, equipped with electric control and provided with an increased upstand on the hinge side

Performance:

- Resistance to permanent loads (Eurocode EN 1993-1-1): 1050 kg/m²
- Sound reduction (EN-ISO140-3): 26 dB
- Watertightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 3000
- Resistance to snow loads (EN 1991-1-3): 3.97kN/m²
- Impact hard body (EN 356): Class P5A
- Impact soft body (EN 13049): Class 5
- Air permeability (EN 12207): Class 3

Standard powder coating:

Roof hatch RHT in special sizes, single lid

Powder coated in RAL7047 (outside) and RAL9010 (inside).

Attention:

- Lid is provided with internal stiffeners, small welding spots can show on outside
- To prevent damage and deformation don't open lid with strong winds.

