

Roof hatch RHT7010 and scissor stair S+

Roof hatch, type RHT7010

Standard opening size: 700 x 1000 mm (Hinge side = long side)

Weight: 56 kg

Product features standard roof hatch RHT:

- Delivered fully assembled
- Thermal separated and insulated construction
- Counterbalancing system for assisted opening and controlled closing
- Double sealing for water and weather tightness
- Diagonal handrail in Gorter yellow on the inside of the lid provides extra grip when stepping in and out
- Fully opened lid engages automatically, with release button
- Closure with Gorter hardware and stainless steel Euro cylinder lock, inside and outside operation

CodeMark certified for Australia & New Zealand

- Australia CM70087, New Zealand CM70088

Performance according to CE (ETA-15/0338):

- Resistance to permanent loads (Eurocode EN 1993-1-1): 1050 kg/m²
- Sound reduction (EN-ISO140-3): 26 dB
- Watertightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 3000
- Resistance to snow loads (EN 1991-1-3): 3.97kN/m²
- Impact hard body (EN 356): Class P5A
- Impact soft body (EN 13049): Class 5
- Air permeability (EN 12207): Class 3



Roof hatch RHT7010 and scissor stair S+

Standard powder coating:

Powder coated in RAL7047 (outside) and RAL9010 (inside).

Scissor stair, type S+ Gorter

Casing:

- For structural opening size (W x L x H): 700 x 1000 x 320 mm

Ceiling height: mm (max. 3000 mm)

to be specified from top of floor to bottom of cover.

Stair:

- Material: cast aluminium
- Size steps: 350 x 140 x 26 mm, anti-skid
- Distance of steps 250 mm, depending on room height
- Horizontal position of steps is adjustable

Projection while opening:

Max. 500 mm at ceiling height 3000 mm (type S+ Gorter)

Hardware:

- Hook and eye
- Handrail prepared for padlock to secure retracted stairs against misuse
- Stair guide control system

