



Wall and ceiling door type U

Wall- ceiling door - Universal

A x A	Weight
250 x 250 mm	3 kg
400 x 400 mm	5 kg
500 x 500 mm	6 kg
600 x 600 mm	8 kg
600 x 800 mm	10 kg
800 x 800 mm	13 kg

Wall door type B

Wall door - Fire resistant

A x A	Weight
400 x 400 mm	15 kg
600 x 600 mm	27 kg
600 x 800 mm	35 kg
800 x 800 mm	44 kg

Fire rating (EN1634-1 and EN13501-2) - Type B

E: 120 minutes

El₁: 20 minutes

El₂: 60 minutes

EW: 120 minutes

Manual and installation instructions wall- / ceiling doors are supplied with the product.

Clear width (A)

Clear width (A) is net opening passage of the wall- ceiling door. Please visit www.gortergroup.com

Cut out opening (B)

Cut out opening (B) should be larger than Clear width (A). See drawings of type U and B on the left of this frame.

Mounting

- » Make sure the door opens and closes properly and does not stick before finally securing the door.
- » Make sure the wall or ceiling is strong enough for fitting the door.

Finishing

For the finishing of the fire resistant wall- or ceiling door see manual.

Material

Wall- and ceiling doors are made of KTL (cathodic dip painting) treated steel and have a powder coating finish in RAL 9010.