

Hoisting hatch, removable roof hatch RHT with flat lids

Certifications:

KOMO:SKG.0372.0503

Special size: x mm

- Special sizes are delivered in aluminium

Product features roof hatch RHT:

- Delivered fully assembled
- Thermal separated and insulated construction
- Stainless steel egg crate closing system
- Double draftproof and watertight seal between edge and lid
- 4 lifting eyes per lid segment

Performance:

- Resistance to permanent load (Eurocode EN 1993-1-1) 125 kg/m²
- Insulation value (EN-ISO10077-2): $U_w \leq 0.276 \text{ W}/(\text{m}^2 \cdot \text{K})$
- Sound insulation (EN-ISO 717-1:2013): 26 dB
- Water tightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 3000
- Resistance to snow load (EN 1991-1-3): 1.25 kN/m²
- Impact hard body (EN 356): Class P5A
- Impact soft body (EN 13049): Class 5
- Air permeability (EN 12207): Class 3

Surface treatment:

Powder coated in RAL 7047 (exterior) and RAL 9010 (interior).



Hoisting hatch, removable roof hatch RHT with flat lids

Important:

- Avoid deformation and damage, do not remove lids in strong winds

