Roof hatch glazed RHTG

Certifications:

CE ETA-18/0831

Code mark certified: Australia CM70087, New Zealand CM70088

Roof hatch type RHTG

Glazed lid, insulated with HR+++ glass

Opening (mm) - Weight:

- RHTG1015: 1000 x 1500 mm / 187 kg
- RHTG1020: 1000 x 2000 mm / 236 kg
- RHTG1025: 1000 x 2500 mm / 285 kg
- RHTG1030: 1000 x 3000 mm / 328 kg

Hinge side = long side

Product features roof hatch RHTG:

- Delivered fully assembled

- Lid with HR+++ edge-to-edge glazing

- Thermal separated and insulated construction
- Safety glass and burglary resistant
- A diagonal Gorter hand rail offers a steady grip when climbing or descending the stairs
- Wind and watertight sealing all around
- 2 powerful electric motors

© Gorter Group™

Roof hatch glazed RHTG

Performance according to CE (ETA-18/0831):

- Insulating value HR+++ glass: U ≤ 0.500 W/(m².K)
- Insulating (EN-ISO10077-2): Uw ≤ 0.83 W/(m².K)

- Sound reduction (EN-ISO140-3): 27 dB

- Watertightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 2400
- Resistance to snow loads (EN 1991-1-3): 5 kN/m²
- Impact (EN 13049): Class 3
- Air permeability (EN 12207): Class 4

Surface treatment:

Powder coated in RAL9005/RAL9010 (outside) and RAL9010 (inside).

We do not recommend the combination with an attic ladder or scissor stairs!

© Gorter Group™