Roof hatch RHTG with fixed stair GS50

Certifications:

CE ETA-18/0831

Aboma certificate

Code mark certified: Australia CM70087, New Zealand CM70088

Roof hatch type RHTG

Glazed lid, insulated with HR+++ glass

Opening (mm) - Weight:

- RHTG1015: 1000 x 1500 mm / 187 kg
- RHTG1020: 1000 x 2000 mm / 236 kg
- RHTG1025: 1000 x 2500 mm / 285 kg
- RHTG1030: 1000 x 3000 mm / 328 kg

Hinge side = long side

Product features roof hatch RHTG:

- Delivered fully assembled

- Lid with HR+++ edge-to-edge glazing

- Thermal separated and insulated construction
- Safety glass and burglary resistant
- A diagonal Gorter hand rail offers a steady grip when climbing or descending the stairs
- Wind and watertight sealing all around
- 2 powerful electric motors

© Gorter Group™

Roof hatch RHTG with fixed stair GS50

Performance according to CE (ETA-18/0831):

- Insulating value Gorter HR+++ glass: U ≤ 0.500 W/(m².K)
- Insulating (EN-ISO10077-2): Uw ≤ 0.83 W/(m².K)

- Sound reduction (EN-ISO140-3): 27 dB

- Watertightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 2400
- Resistance to snow loads (EN 1991-1-3): 5 kN/m²
- Impact (EN 13049): Class 3
- Air permeability (EN 12207): Class 4

Surface treatment:

Powder coated in RAL 9005/RAL 9010 (outside) and RAL 9010 (inside).

Fixed stair, type GS50 Gorter
Gorter complete assembled. Aluminium, anodized.

Floor height: ..... mm

- Pitch adjustable from 50°- 66°
- Standard room height 2500 mm (50°) - 3000 mm (66°)

Step:

- Size 730 x 175 x 45 mm
- With anti skid profile

© Gorter Group™

Roof hatch RHTG with fixed stair GS50

Accessories:

- Brackets for fixation on floor and in roof or ceiling opening
- 2 Handrails complete with poles.

IMPORTANT: ready for installation on site

© Gorter Group™