

# Complete roof access, RHTS1015 - for room height up to 3000 mm

Certifications: CE ETA-15/0338

Dimensions (opening to attic): 1000x1500 mm (width x length)

Weight: 197 kg

## Product features roof hatch RHTS:

- Delivered fully assembled
- Thermally broken and insulated construction
- Opening mechanism: Counterbalanced system with assisted opening and controlled closing
- Automatic locking in open position, one-hand release
- Closure with Gorter hardware and stainless steel Euro cylinder lock, operated from inside and outside
- Supplied with clamping strips for fixing roofing material
- Wind and weather-tight perimeter seal between lid and curb
- Diagonal handrail in Gorter-Yellow on the inside of the lid, offers extra grip when entering and exiting
- Spring mechanism for easy operation of the scissor stairs

## Performance:

- Resistance to permanent load (Eurocode EN 1993-1-1): 1050 kg/m<sup>2</sup>
- Thermal insulation value (EN-ISO 6946):  $U_{tot} \leq 0.095 \text{ W}/(\text{m}^2 \cdot \text{K})$
- Sound insulation (EN-ISO140-3): 26 dB
- Watertightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 3000
- Resistance to snow load (EN 1991-1-3): 3.97 kN/m<sup>2</sup>
- Impact hard body (EN 356): Class P5A
- Impact soft body (EN 13049): Class 5
- Air permeability (EN 12207): Class 3

Powder coating: Outside: Powder coating in RAL7047 Inside: Recycled PET in white RAL 9010



# Complete roof access, RHTS1015 - for room height up to 3000 mm

Casing: Dimensions (W x L x H):

RHTS1015 1000 x 1500 x 1000 mm

Room height: ..... mm (up to 3000 mm)

Scissor stairs:

- Material: Cast aluminium
- Steps with anti-slip profiling
- Step size: 480 x 140 x 26 mm
- Horizontal position of steps is adjustable

Projection:

Max. 600 mm at room height 3000 mm

Accessories (included):

- Control rod
- Handrail
- Spring mechanism for easy operation