Complete roof access, RHTS7014-H - for room height up to 3500 mm

Certifications: *CE ETA-15/0338*

Dimensions (opening to roof): 700 x 1400 mm (Width x Length)

Weight: 165 kg

Product features RHTS roof hatch:

- Delivered fully assembled
- Thermally broken and insulated construction
- Opening mechanism: Counter-balance system with assisted opening and fall-back inhibition
- Automatic locking in the open position, one-hand release
- Closure with Gorter hardware and stainless steel Euro cylinder lock, operation from inside and outside
- Supplied with clamping strips for fixing the roofing membrane
- Wind and weather-tight perimeter seal between lid and curb
- Diagonal handrail in Gorter-Yellow on the inside of the lid, provides additional grip when entering and exiting
- Spring mechanism for easy operation of the scissor stairs

Performance:

- Resistance to permanent loading (Eurocode EN 1993-1-1): 1050 kg/m²
- Thermal insulation value (EN-ISO 6946): $U_{tot} \leq 0.095$ W/(m^2.K)
- Sound insulation (EN-ISO140-3): 26 dB
- Watertightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 3000
- Resistance to snow load (EN 1991-1-3): 3.97 kN/m²
- Hard body impact (EN 356): Class P5A
- Soft body impact (EN 13049): Class 5
- Air permeability (EN 12207): Class 3

Powder coating: Exterior: Powder coating in RAL7047 Interior: Recycled PET in white RAL 9010

© Gorter Group™

Complete roof access, RHTS7014-H - for room height up to 3500 mm

Casing: Dimensions (W x L x H):

RHTS1014-H 700 x 1400 x 1000 mm

Room height: ..... mm (max. 3500 mm)

Scissor stairs:

- Material: Die-cast aluminum
- Steps with anti-slip profiling
- Step size: 480 x 140 x 26 mm
- Horizontal position of the steps is adjustable

Extension clearance:

Max. 950 mm at room height 3500 mm

Accessories (included):

- Control rod
- Handrail
- Spring mechanism for easy operation

© Gorter Group™